AustinSprings^T clear. Refreshing. Pure.

Performance Data for the Austin Springs Shower Filter					
Model	Replacement	Operating pressure range	Rated capacity	Max operating temp	Rated flow
AS-SH-P-W	AS-SH-P-R	80 psi	10,000 gallons	115° F	2.5 gpm

This system has been tested according to NSF/ANSI 177 for reduction of free available chlorine. The concentration of free available chlorine in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system, as specified in NSF/ANSI 177. This system has not been evaluated for free available chlorine reduction performance in the presence of chloramines. Free available chlorine reduction performance may be impacted by the presence of chloramines in the water supply. Please contact your local water utility to determine if chloramines are used in treating your water.

Testing was performed under standard laboratory conditions, actual performance may vary. See preceeding page for general installation conditions and needs.

This filter system is designed and tested for use with genuine Austin Springs parts, including replacement filters and all hardware. Use of parts from other manufacturers may result in loss of contaminant reduction performance, system damage or failure. Use of parts from other manufacturers will also void your warranty. Please visit your original retail location for all replacement parts.

The Austin Springs shower filtration system is designed to produce the highest quality water possible with the least amount of pressure loss. Austin Springs' patented two-stage filter cartridge substantially reduces chlorine and other chemicals present in tap water. In compliance with California State Law, this system has a maximum flow rate of 2.5 gallons per minute. The filter cartridge should be replaced every six months per instructions.

Do not use with water that is microbiologically unsafe or of unknown water quality without adequate disinfection before or after the system.

This system and installation shall comply with applicable state and local regulations.

This system is not for use as a drinking water treatment unit.

Austin Springs

1609 Shoal Creek #200, Austin, Texas 78701 866-238-5855 • www.AustinSprings.com Manufactured in Facility 1

AS-SH-P-W_install_2013021

Installation Instructions

Premium Shower Filter with Wand Model: AS-SH-P-W

